


WLC® Wafer Check Valves



The DFT® Model WLC Wafer style Silent Check Valve is a lightweight, spring-assisted, in-line check valve that provides reliable, low maintenance service for a wide range of fluids and pressure/temperature combinations. The joint between the seat ring and body is sealed by the flange gasket upon installation preventing any leakage through the joint when the valve is in service.

Size/Class

- 1", 1 1/2" - 150/300
- 2" to 8" - 150/300
- 10" - 150

Results 1 - 61 of 61

Prod. #	Class	Size	Dimension A	Dimension B	Cv	Cracking Pressure CP	Body
9030-1	150/300	1 in	2.00 in 51 mm	2.88 in 73 mm	19	0.36 psig 0.025 bar	A216 Grade WCB
9033-1	150/300	1 in	2.00 in 51 mm	2.88 in 73 mm	19	0.36 psig 0.025 bar	A351 CF8M
9034-1	150/300	1.5 in	2.50 in 64 mm	3.75 in 95 mm	36	0.17 psig 0.012 bar	A216 Grade WCB
9035-1	150/300	1.5 in	2.5 in 64 mm	3.75 in 95 mm	36	0.17 psig 0.012 bar	A351 CF8M
9012	600	DN 25 1 in	2.38 in 60 mm	2.88 in 73 mm	19	0.36 psig 0.025 bar	A105
9013	600	DN 25 1 in	2.38 in 60 mm	2.88 in 73 mm	19	0.36 psig 0.025 bar	A479-316
9038	900/1500	DN 25 1 in	2.38 in 60 mm	3.13 in 80 mm	19	0.44 psig 0.030 bar	A105
9041	900/1500	DN 25 1 in	2.38 in 60 mm	3.13 in 80 mm	19	0.44 psig 0.030 bar	A479-316
9130	1500 (RTJ)	DN 25 1 in	2.38 in 60 mm	3.13 in 80 mm	19	0.44 psig 0.030 bar	A105
9131	1500 (RTJ)	DN 25 1 in	2.38 in 60 mm	3.13 in 80 mm	19	0.44 psig 0.030 bar	A479-316
9097	600	DN 40 1.5 in	2.88 in 73 mm	3.75 in 95 mm	23	0.44 psig 0.030 bar	A105
9019	600	DN 40 1.5 in	2.88 in 73 mm	3.75 in 95 mm	23	0.44 psig 0.030 bar	A479-316
9044	900/1500	DN 40 1.5 in	2.88 in 73 mm	3.88 in 99 mm	23	0.54 psig 0.037 bar	A105
9045	900/1500	DN 40 1.5 in	2.88 in 73 mm	3.88 in 99 mm	23	0.54 psig 0.037 bar	A479-316
9132	1500 (RTJ)	DN 40 1.5 in	2.88 in 73 mm	3.88 in 99 mm	23	0.54 psig 0.037 bar	A105
9133	1500 (RTJ)	DN 40 1.5 in	2.88 in 73 mm	3.88 in 99 mm	23	0.54 psig 0.037 bar	A479-316
9003	150/300	DN 50 2 in	2.63 in 67 mm	4.38 in 111 mm	57	0.24 psig 0.017 bar	A216 WCB
9004	150/300	DN 50 2 in	2.63 in 67 mm	4.38 in 111 mm	57	0.24 psig 0.017 bar	A351 CF8M
9006	600	DN 50 2 in	2.38 in 60 mm	4.25 in 108 mm	53	0.26 psig 0.018 bar	A216 Grade WCB
9007	600	DN 50 2 in	2.38 in 60 mm	4.25 in 108 mm	53	0.26 psig 0.018 bar	A351 CF8M
9009	900/1500	DN 50 2 in	2.75 in 70 mm	5.50 in 140 mm	48	0.24 psig 0.017 bar	A216 Grade WCB
9010	900/1500	DN 50 2 in	2.75 in 70 mm	5.50 in 140 mm	48	0.24 psig 0.017 bar	A351 CF8M

9086	1500 (RTJ)	DN 50 2 in	3.13 in 80 mm	5.50 in 140 mm	48	0.24 psig 0.017 bar	A216 Grade WCB
9091	1500 (RTJ)	DN 50 2 in	3.13 in 80 mm	5.50 in 140 mm	48	0.24 psig 0.017 bar	A351 CF8M
9014	150/300	DN 65 2.5 in	2.88 in 73 mm	5.13 in 130 mm	95	0.37 psig 0.026 bar	A216 Grade WCB
9015	150/300	DN 65 2.5 in	2.88 in 73 mm	5.13 in 130 mm	95	0.37 psig 0.026 bar	A351 CF8M
9025	150/300	DN 80 3 in	3.13 in 80 mm	5.75 in 146 mm	140	0.19 psig 0.013 bar	A216 Grade WCB
9026	150/300	DN 80 3 in	3.13 in 80 mm	5.75 in 146 mm	140	0.19 psig 0.013 bar	A351 CF8M
9028	600	DN 80 3 in	2.88 in 73 mm	5.75 in 146 mm	133	0.26 psig 0.018 bar	A216 Grade WCB
9029	600	DN 80 3 in	2.88 in 73 mm	5.75 in 146 mm	133	0.26 psig 0.018 bar	A351 CF8M
9031	900/1500	DN 80 3 in	3.25 in 83 mm	6.75 in 171 mm	113	0.19 psig 0.013 bar	A216 Grade WCB
9032	900/1500	DN 80 3 in	3.25 in 83 mm	6.75 in 171 mm	113	0.19 psig 0.013 bar	A351 CF8M
9088	1500 (RTJ)	DN 80 3 in	3.25 in 83 mm	6.75 in 171 mm	113	0.19 psig 0.013 bar	A216 Grade WCB
9093	1500 (RTJ)	DN 80 3 in	3.25 in 83 mm	6.75 in 171 mm	113	0.19 psig 0.013 bar	A351 CF8M
9036	150/300	DN 100 4 in	4.00 in 102 mm	7.09 in 180 mm	265	0.19 psig 0.013 bar	A216 Grade WCB
9037	150/300	DN 100 4 in	4.00 in 102 mm	7.09 in 180 mm	265	0.19 psig 0.013 bar	A351 CF8M
9039	600	DN 100 4 in	3.13 in 80 mm	7.50 in 191 mm	234	0.49 psig 0.034 bar	A216 Grade WCB
9040	600	DN 100 4 in	3.13 in 80 mm	7.50 in 191 mm	234	0.49 psig 0.034 bar	A351 CF8M
9042	900/1500	DN 100 4 in	4.00 in 102 mm	8.13 in 207 mm	211	0.46 psig 0.032 bar	A216 Grade WCB
9043	900/1500	DN 100 4 in	4.00 in 102 mm	8.13 in 207 mm	211	0.46 psig 0.032 bar	A351 CF8M
9089	1500 (RTJ)	DN 100 4 in	4.13 in 105 mm	8.25 in 210 mm	211	0.46 psig 0.032 bar	A216 Grade WCB
9094	1500 (RTJ)	DN 100 4 in	4.13 in 105 mm	8.25 in 210 mm	211	0.46 psig 0.032 bar	A351 CF8M
9047	150/300	DN 125 5 in	4.63 in 118 mm	9.81 in 249 mm	360	0.29 psig 0.020 bar	A216 Grade WCB
9048	150/300	DN 125 5 in	4.63 in 118 mm	9.81 in 249 mm	360	0.29 psig 0.020 bar	A351 CF8M
9058	150/300	DN 150 6 in	5.50 in 140 mm	9.88 in 251 mm	506	0.45 psig 0.031 bar	A216 Grade WCB
9059	150/300	DN 150 6 in	5.50 in 140 mm	9.88 in 251 mm	506	0.45 psig 0.031 bar	A351 CF8M
9061	600	DN 150 6 in	5.38 in 137 mm	10.38 in 264 mm	441	0.66 psig 0.046 bar	A216 Grade WCB
9062	600	DN 150 6 in	5.38 in 137 mm	10.38 in 264 mm	441	0.66 psig 0.046 bar	A351 CF8M
9064	900/1500	DN 150 6 in	6.25 in 159 mm	11.25 in 286 mm	370	0.58 psig 0.040 bar	A216 Grade WCB
9065	900/1500	DN 150 6 in	6.25 in 159 mm	11.25 in 286 mm	370	0.58 psig 0.040 bar	A351 CF8M
9090	1500 (RTJ)	DN 150 6 in	6.25 in 159 mm	11.25 in 286 mm	370	0.58 psig 0.040 bar	A216 Grade WCB
9095	1500 (RTJ)	DN 150 6 in	6.25 in 159 mm	11.25 in 286 mm	370	0.58 psig 0.040 bar	A351 CF8M
9071	150/300	DN 200 8 in	6.50 in 165 mm	12.13 in 308 mm	860	0.56 psig 0.039 bar	A216 Grade WCB
9072	150/300	DN 200 8 in	6.50 in 165 mm	12.13 in 308 mm	860	0.56 psig 0.039 bar	A351 CF8M
9074	1500	DN 200 8 in	8.13 in 207 mm	13.81 in 351 mm	620	0.66 psig 0.046 bar	A216 Grade WCB

9084	150	DN 250 10 in	8.25 in 210 mm	17.63 in 448 mm	1355	0.45 psig 0.031 bar	A216 Grade WCB
9085	150	DN 250 10 in	8.75 in 222 mm	17.63 in 448 mm	1355	0.45 psig 0.031 bar	A351 CF8M
9053	1500	DN 250 10 in	9.75 in 248 mm	17 in 432 mm	755	0.61 psig 0.042 bar	A216 Grade WCB
9054	1500	DN 250 10 in	9.75 in 248 mm	17 in 432 mm	755	0.61 psig 0.042 bar	A351 CF8M
9049	1500 (RTJ)	DN 250 10 in	9.75 in 248 mm	17.06 in 433 mm	755	0.61 psig 0.042 bar	A216 Grade WCB
9052	1500 (RTJ)	DN 250 10 in	9.75 in 248 mm	17.06 in 433 mm	755	0.61 psig 0.042 bar	A351 CF8M

Results 1 - 61 of 61