

AWT-100 Accessories



GTC-720

Flexible Shafts

To order flexible shaft(s), determine tube I.D.(s) and length of longest tubes. Order flexible shaft(s) to correspond with tube I.D.(s) and lengths. (Consult factory for longer flexible shafts if required.)

Flexible Shafts (Nylon Casing) for Tubes 1" (25.4mm) I.D. and Up

GTC-720-15 Flexible Shaft 15' (4.6m)

GTC-720-35 Flexible Shaft 35' (10.7m)

GTC-720-25 Flexible Shaft 25' (7.6m)

GTC-720-50 Flexible Shaft 50' (15.2m)



Wheel Brush Assembly

Recommended for removing soft and light scale deposits. Each assembly consists of a single stainless steel wire wheel brush attached to each end of a universal joint. Brushes should be 1/4"-3/8" (6.4-9.5mm) smaller than tube I.D.

* Note: GTC-706 Coupling (\$5.00) required to connect to GTC-720, GTC-721, GTC-721G and GTC-821 Flexible Shafts.

Wheel Brush Assemblies

Curved Tube I.D.	Wheel Brush Assembly	Actual Brush O.D.	Replacement Brushes
1 1/4" - 1 3/8" (32-35mm)	WBC-100*	1" (25.4mm)	WBR-100
1 1/2" - 1 5/8" (38-41mm)	WBC-125*	1 1/4" (32mm)	WBR-125
1 3/4" - 1 7/8" (45-48mm)	WBC-150*	1 1/2" (38mm)	WBR-150
2" - 2 1/8" (51-54mm)	WBC-175	1 3/4" (45mm)	WBR-175
2 1/4" - 2 3/8" (57-60mm)	WBC-200	2" (51mm)	WBR-200
2 1/2" - 2 5/8" (64-67mm)	WBC-225	2 1/4" (57mm)	WBR-225
2 3/4" - 2 7/8" (70-73mm)	WBC-250	2 1/2" (64mm)	WBR-250
3" - 3 1/8" (76-79mm)	WBC-275	2 3/4" (70mm)	WBR-275
3 1/4" - 3 1/2" (83-89mm)	WBC-300	3" (76mm)	WBR-300



Single Cone Cutter Assembly

Recommended for removing scale deposits. Assemblies consist of one or two cone elements and should be slightly smaller than tube I.D. The innovative design of the cones ensures a thorough cleaning. In watertube boilers, cone cutters are the most effective cleaning tools for all conditions.

Cone Cutter Assemblies

Straight Tube I.D.	Curved Tube I.D.	Single Cone Assembly	Double Cone Assembly	Replacement Cones
1 1/8" - 1 1/4" (29-32mm)	1 1/4" - 1 3/8" (32-35mm)	SCA-100	DCA-100	RCO-100
1 5/16" - 1 3/8" (33-35mm)	1 1/2" - 1 5/8" (38-41mm)	SCA-112	DCA-112	RCO-112
1 7/16" - 1 1/2" (37-38mm)	1 3/4" - 1 7/8" (45-48mm)	SCA-125	DCA-125	RCO-125
1 9/16" - 1 3/4" (40-45mm)	2" - 2 1/8" (51-54mm)	SCA-150	DCA-150	RCO-150
1 3/8" - 2" (46-51mm)	2 1/4" - 2 3/8" (57-60mm)	SCA-175	DCA-175	RCO-175
2 1/16" - 2 5/16" (52-59mm)		SCA-200	DCA-200	RCO-200



Double Cone Cutter Assembly

Flex Hub Tools

Flex Hub Tools incorporate centrifugally activated blades for removing hard and heavy deposits in straight or curved tubes. A drill can be attached to the front of the GTC-227 or GTC-231 Flex Hub to clean severely clogged tubes.

GTC-226 Flex Hub for straight tubes 7/8"-1 1/2" (22.2-38mm) I.D. or curved tubes 1"-1 3/4" (25.4-45mm) I.D.

GTC-231 Flex Hub for straight tubes 1 1/2"-2" (38-51mm) I.D. or curved tubes 1 3/4"-2 1/2" (45-64mm) I.D.

GTC-227 Flex Hub for straight tubes 1 3/4"-3" (45-76mm) I.D. or curved tubes 2 1/2"-3" (64-76mm) I.D.

GTC-226A Replacement Metal Blades for GTC-226 (set of three)

GTC-231A Replacement Metal Blades for GTC-231 (set of three)

GTC-227A Replacement Metal Blades for GTC-227 (set of three)

GTC-229 Drill to be attached to GTC-227 Flex Hub

GTC-231D Drill to be attached to GTC-231 Flex Hub

CUJ-002 Universal Joint for use with Flex Hubs when minimum tube bend radius is less than 5 x I.D. of the tube (consult factory)

Flexible Shaft Repair Kits

Flexible shaft repair kits include 4 drive end repair couplings, 4 thrust washers, 4 tool end repair couplings, 1 crimping tool with punch, 1 flexible shaft lubricator with quick disconnect, and 2 bottles [16 ounces (0.5 liter) each] of lubricant for flexible shaft lubricator.

REP-720-KIT For GTC-720 Shafts



Flex Hub Tool



Flexible Shaft Repair Kit

Note: Call for additional cleaning tools and accessories.